

**Amendments to the Specification:**

Please replace paragraph [0011] with the following amended paragraph:

[0011] The present invention provides a convertible top for a vehicle having a vehicle body comprising: a backlite having a first position corresponding to a retracted position of the convertible top and a second position corresponding to ~~an~~ a deployed position of the convertible top; a floating bow connected to the backlite, the floating bow having a raised position when the backlite is in the ~~first position~~ second position and a lowered position when the backlite is in the ~~second position~~ first position; and an attachment device for connecting the floating bow to the vehicle body, the attachment device including a base section attachable to the vehicle body and an adjustment section connected to the floating bow and moveable with respect to the base section for adjusting the raised position of the floating bow.

Please replace paragraph [0032] with the following amended paragraph:

[0032] As shown in Figs. 3 and 4, strap 30 is connected to adjustment section of attachment device 40 at moveable nut 42 by a pair of rods 32. Strap 30 can thus rotate with respect to rods 32 at the connection. Moveable nut 42 has interior threads 49 that interact with exterior threads 51 of an adjustment screw 44 of the adjustment section. Nut 42 is rotationally fixed but translationally moveable with respect to a base section 46 via the interaction of a flat section 47 of base section ~~47~~ 46 with tongs 43 of nut 42. The position of rods 32 with respect to the base 46 and thus vehicle body 10 can be set by turning a head portion 52 of screw 44, which causes nut 42 to translate with respect to base 46.